

# Technical data sheet

## Universal clamp for PV module mounting

Item number: 5901010



Universal clamp to mount photovoltaic modules on flat and pitched roofs, suitable as a clamp between 2 modules or as an end clamp. Lockable pre-fastening on TP 45 support profile and on STK and STL supports. Suitable for 10 mm slot width. Can be rotated through 90° after engaging. Lockable fastening of the PV module with Torx 30 wrench.



**A2** Stainless steel

**BK** Bright

### Master data

Item number	5901010
Type	KLU A2
Description 1	Universal clamp
Description 2	for flat/pitched roof systems
Manufacturer	OBO
Dimension	41x42x79
Material	Stainless steel
Surface	Bright
Surface standard	
Smallest sales unit	20
Unit of quantity	Piece
Weight	6.59 kg
Weight unit	kg/100 pc.


# Technical data sheet

## Universal clamp for PV module mounting

Item number: 5901010



### Dimensions



Width	43 mm
Height	79 mm

### Technical data

With fastening material	no
Depth	42 mm
Photovoltaic connection and fastening element version	Universal clamp
For frame height min.	30 mm
For frame height max.	50 mm
Torsion spring stiffness (k.rot.y)	0
Torsion spring stiffness (k.rot.z)	0
With module earthing	no