

Technical data sheet

Height-adjustable cassette for inspection opening, RKN, brass

Item number: 7408956



"Blank" height-adjustable cassette for the creation of an inspection opening of nominal size 4. Installation of devices in duct systems, raised and cavity floors in interior dry or wet-care floors. Only suitable for smooth floor coverings. For the installation of two UT3 universal supports for four single devices with support ring/support clamp or six Modul 45@ devices. 2 APMT2 cover plates can be installed.



Master data

| | |
|---------------------|-----------------|
| Item number | 7408956 |
| Type | RKN3 4 MS 25 |
| Description 1 | Square cassette |
| Description 2 | Blank lid |
| Manufacturer | OBO |
| Dimension | 199x199x105 |
| Material | Brass |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 240 kg |
| Weight unit | kg/100 pc. |


Technical data sheet

Height-adjustable cassette for inspection opening, RKN, brass

Item number: 7408956



Dimensions



| | |
|-------------|--------|
| Length | 199 mm |
| Width | 199 mm |
| Height | 110 mm |
| Dimension h | 110 mm |



Technical data

| | |
|--|-----------------|
| Number of installable devices | 0 |
| Number of cable outlets | 0 |
| Number of universal supports | 2 x UT3 |
| Version for | Square |
| Cable outlet version | No cable outlet |
| Floor cut-out / Mounting opening | 201x201 |
| Floor care | Wet |
| Decouplable | no |
| Floor height, max. | 155 mm |
| Floor height, min. | 110 mm |
| Suitable for raised floor installation | yes |
| Suitable for cavity floor installation | yes |
| Suitable for underfloor box | 250/350 |
| Device support to accept mounting boxes | no |
| Length of installation dimensions | 201 mm |
| Nominal size for device installation units | 4 |
| Height-adjustment range, max. | 155 mm |
| Height-adjustment range, min. | 110 mm |
| Standard | EN 50085-2-2 |
| Protection rating (IP) when used | IP00 |
| Protection rating (IP) when unused | IP55 |
| Protection rating IK code | IK10 |
| Heavy-duty version | no |
| Installation system type | UT3 |
| Vertical load, large area | to 15,000 N |
| Vertical load, small area | to 3,000 N |
| Approvals | VDE |
| Floor covering thickness | 25 mm |