

Technical data sheet

Insulated air-termination rod for inner-routed isCon® conductor

Item number: 5408854



- For routing OBO isCon® conductors in pipes
- For installation on the building structure with isFang support
- Suitable for wind loads according to Eurocode 1: DIN EN 1991-1-4
- Tested according to VDE V 0185-561-8 (IEC TS 62561-8)
- Aluminium standpipe and air-termination tip
- Centre section made of fibre-glass reinforced plastic (GRP)



GFK Fibre-glass-reinforced plastic

Master data

Item number	5408854
Description 1	Insulated interception rod
Description 2	for isCon conductor, internal
Manufacturer	OBO
Dimension	4000mm
Material	Fibre-glass-reinforced plastic
Smallest sales unit	1
Unit of quantity	Piece
Weight	535.741 kg
Weight unit	kg/100 pc.


Technical data sheet

Insulated air-termination rod for inner-routed isCon® conductor

Item number: 5408854



Dimensions	
Length	4,000 mm
Dimension A	1,325 mm
Dimension B	1,000 mm
Dimension d min.	50 mm
Dimension H	1,500 mm
Dimension L	4,000 mm



Technical data	
Connection	Round conductor
Version for	Air-termination rod
High voltage-resistant, insulated version	yes